STANDARDS OF PERFORMANCE OF RVPN FOR THE YEAR 2014-15
In pursuance of Sec 59(2) of the Electricity Act 2003, the Standards of Performance achieved by Rajasthan Rajya Vidyut Prasaran Nigam Lmited Jaipur, during the year 2014-2015, as compared to various parameters specified in the Regulations are

S. No		Voltage Level of Performance specified by the Commission		y the	Actual Performance Level attained by RVPN		Inference Inferior/Superior		
1	System Availability	132 kV		98%		99.78%		Superior	
		33 kV	98% 98%		99.66% 99.79%		Superior Superior		
		11 kV							
2	Voltage Profile		Max.	Min.	Max.	Min.	Max.	Min.	
		400 kV	420	360	444	365			
		220 kV	245	200	255	175	Inf.	Sup.	
		132 kV	145	120	150	109	Inf.	Inf.	
		33 kV	34.98	30.03	37.0	27	Inf.	Inf.	
		11 kV	11.66	10.01	13.0	9.2	Inf.	Inf.	
3	Voltage Unbalance	400 kV	2.00%		2.00%				
		220 kV	2.00%		2.55%		Inferior Inferior		
		132 kV		3.00%		2,99%		Superior	
		33 kV		3.00%		4.10%		Inferior	
		11 kV	3.00%		1.84%		Superior		
4	Voltage Variation				For Higher	For Lower	J Sup	erioi	
	Index				Voltage	Voltage			
		400 kV	+	1.125%	3.74	1.69	 		
	1	220 kV	- 	±1%	2.60	1.30	Inf.	Inf.	
]	132 kV	-	±1%	1.23	1.49	Inf.	Inf.	
		33 kV	±1%		1.54	1.37	Inf.	Inf.	
		11 kV		±1%	1.39	1.33	inf.	Inf.	
5	Frequency Variation Index	As per IEGC			0.23		-		
6	Loss of Load Expectation (LOLE)		- 2.00%		Nit		Superior		
7	System Average	132 kV	18 Nos/year		7.13 Nos.		Superior		
	Interruption	33 kV	18 Nos/year		12.85 Nos.		Superior		
	Frequency Index (SAIFI)	11 kV	18 Nos/year	18 Nos/year		2.05 Nos.		Superior	
8	System Average 132 kV		8 Hrs/year			2.91 Hrs.		Superior	
	Interruption	33 kV	8 Hrs/year		4.57 Hrs.		Superior		
$\overline{}$	Duration Index (SAIDI)	11 kV	8 Hrs/year	8 Hrs/year		0.92 Hrs.		Superior	
9	Total Harmonic IEC Std. 1000-4-7 or			3.16		Inferior			
	Distortion (THD)	IEEE Std. 51: Not to exceed point) 1% at EHV interconnected						
0	Current Unbalance	400 kV	3%		14.05		Inferior		
\dashv		220 kV	3%		12.46		Inferi		
_		132 kV	3%		6.72		Inferi		
\bot		33 kV	3%		11.84		Inferior		
		11 kV 3%.			4.84		Inferior		

Note: (i) The above information is as received from RVPN.

(ii) The Loss of Load Expectation (LOLE) during 2014-15 due to system inadequacy may be treated as NIL.

(iii) The authenticity of figures in respect of voltage profile, voltage un-balance and voltage variation index are based on manual readings of Analogue meters as per intimation received from RVPN.

> (G. K. Sharma) Secretary